Appl. No. 09/728,453   PATENT
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1.   (Currently amended): A method <u>performed by a presentation recorder device</u> of communicating information received during a multimedia presentation, comprising:

       ~~providing an adapter comprising a transceiver;~~

       receiving[[,]] ~~at the adapter,~~ <u>first information at the presentation recorder device from a first system, the first information including</u> at least one of video information or audio information ~~from a first system, the at least one of video information or audio information~~ generated from a presentation file;

       receiving[[,]] ~~at the adapter,~~ <u>second information at the presentation recorder device, the second information including</u> at least one of <u>video information or audio information</u> ~~audio or video information~~ from a capture device, the <u>second</u> information captured by the capture device during the multimedia presentation;

       ~~differencing between a first video frame and a second video frame, at the adapter, of the video information received from the first system or the capture device~~ <u>analyzing video information received from the first system or video information received from the capture device at the presentation recorder device to determine a difference between a first video frame and a second video frame</u>;

       selecting ~~based on the differencing, at the adapter,~~ a set of one or more keyframes <u>at the presentation recorder device</u> from the <u>analyzed</u> video information received from the first system or the <u>analyzed video information received from the</u> capture device in response to a user-configurable threshold <u>and the difference between a first video frame and a second video frame</u>; ~~and~~

22   analyzing the first information and the second information at the presentation

23 recorder device to extract textual information from the first information or the second

24 information using one or more text recognition techniques;

25   generating a presentation representation at the presentation recorder device of the

26 first information and the second information, the presentation representation including a

27 representation of each keyframe in the set of keyframes and the textual information extracted by

28 the presentation recorder device from the first information or the second information;

29   communicating[[,]] from the adapter using the transceiver, at least a portion of the

30 presentation representation from the presentation recorder device to one or more devices, the

31 communicated portion of the presentation representation including one or more keyframes from

32 the set of keyframes and a portion of the textural information.

1   2.   (Currently amended): The method of claim 1[[:]] further comprising:

2   synchronizing [[the]] audio information at the presentation recorder device

3   received from the first system or from the capture device at the adapter with the selected set of

4   keyframes.

1   3.   (Currently amended): The method of claim 1 further comprising:

2   storing the set of keyframes in a memory associated with the presentation recorder

3   device coupled to the adapter.

1   4.   (Currently amended): The method of claim 3 further comprising:

2   receiving[[,]] at the adapter, a request at the presentation recorder device from a

3   device requesting transmission of a first portion of the one or more keyframes in the set of

4   keyframes;

5   in response to the request, determining at the presentation recorder device the first

6   portion of the one or more keyframes in the set of keyframes requested by the device and

7   corresponding audio information; and

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

8   wherein communicating at least a portion of the presentation representation

9   further comprises transmitting the ~~first portion of the set of keyframes and~~ corresponding audio

10   information from the presentation recorder device to the device.

1   5.   (Currently amended): The method of claim 4 wherein the request received

2   from the device requests transmission of a portion of the first information received by the ~~adapter~~

3   presentation recorder device from the first system.

1   6.   (Currently amended): The method of claim 4 wherein the request received

2   from the device requests transmission of a portion of the second information received by the

3   ~~adapter~~ presentation recorder device from the capture device.

1   7.   (Currently amended): The method of claim 4 wherein the request received

2   from the device requests transmission of audio information from the first information or the

3   second information received by the ~~adapter~~ presentation recorder device.

1   8.   (Currently amended): The method of claim 4 wherein the request received

2   from the device requests transmission of video information from the first information or the

3   second information received by the ~~adapter~~ presentation recorder device.

1   9.   (Currently amended): The method of claim 4 wherein the request received

2   from the device requests transmission of audio or video information received by the ~~adapter~~

3   presentation recorder device from the first system and the capture device between a start time

4   and an end time.

1   10.   (Currently amended): The method of claim 1 further comprising:

2   ~~processing, at the adapter, the information received from the first system and the~~

3   ~~information received from the capture device to generate a first representation;~~

4   ~~wherein communicating the information from the adapter further comprises~~

5   ~~transmitting at least a portion of the first representation from the adapter;~~

6   ~~wherein processing the information received from the first system and the~~

7   ~~information received from the capture device to generate the first representation comprises:~~

8   selecting ~~a plurality of video~~ the one or more key frames at the presentation

9   recorder device from video information in the first information or the second information

10   ~~received by the adapter;~~

11   synchronizing the ~~plurality of video~~ the one or more keyframes at the presentation

12   recorder device with audio information received from the first system and with audio

13   information received from the capture device ~~received by the adapter;~~ and

14   storing third ~~information related to~~ associating the ~~plurality of video~~ one or more

15   keyframes with the audio information received from the first device, the audio information

16   received from the capture device, and the portion of the textual information.

1   11.   (Currently amended): The method of claim 10[[:]] ~~wherein processing the~~

2   ~~information received from the first system and the information received from the capture device~~

3   ~~to generate the first representation~~ further ~~comprises~~ comprising:

4   generating a web page for each ~~video~~ keyframe in the ~~plurality of video~~ one or

5   more keyframes, each web page including a video frame;

6   assigning a uniform resource locator (URL) to each web page; and

7   wherein ~~transmitting~~ communicating at least a portion of the ~~first~~ presentation

8   representation comprises transmitting at least one URL assigned to a web page.

1   12.   (Currently amended): The method of claim 11 ~~wherein transmitting at~~

2   ~~least a portion of the first representation comprises~~ further comprising:

3   receiving[[,]] ~~at the adapter,~~ a request at the presentation recorder device from a

4   device identifying a first URL;

5   in response to the request, determining at the presentation recorder device a first

6   web page corresponding to the first URL; and

7   wherein communicating at least a portion of the presentation representation

8   comprises transmitting the first web page from the presentation recorder device to the device.

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

1   13.   (Currently amended): The method of claim 1 wherein selecting the set of
2 one or more keyframes <u>at the presentation recorder device</u> in response to the user-configurable
3 threshold comprises selecting <u>at the presentation recorder device</u> frames of video at a
4 predetermined sampling interval.

1   14.   (Currently amended): A computer program product stored on a computer
2 readable medium and executed by an adapter for communicating information received during a
3 multimedia presentation, comprising:

4   code for receiving <u>first</u> information <u>at the adapter</u> from a first system, the <u>first</u>
5 information comprising at least one of video information or audio information generated from a
6 presentation file;

7   code for receiving <u>second information at the adapter from a capture device, the</u>
8 <u>second information including at least one of video information or audio information</u> ~~at least one~~
9 ~~of audio or video information from a capture device, the at least one of audio or video~~
10 ~~information~~ captured by the capture device during the multimedia presentation;

11   code for ~~differencing between a first video frame and a second video frame of the~~
12 ~~video information received from the first system or the capture device~~ <u>analyzing video</u>
13 <u>information received from the first system or video information received from the capture device</u>
14 <u>at the presentation recorder device to determine a difference between a first video frame and a</u>
15 <u>second video frame</u>;

16   code for selecting ~~based on the differencing, at the adapter,~~ a set of one or more
17 keyframes from the <u>analyzed</u> video information received from the first system or <u>analyzed video</u>
18 <u>information received from</u> the capture device <u>at the adapter</u> in response to a user-configurable
19 threshold; ~~and~~

20   <u>code for analyzing the first information and the second information at the adapter</u>
21 <u>to extract textual information from the first information or the second information using one or</u>
22 <u>more recognition techniques;</u>

23   <u>code for generating a presentation representation at the adapter of the first</u>
24 <u>information and the second information, the presentation representation including a</u>

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

25   representation of each keyframe in the set of keyframes and the textual information extracted by

26   the adapter from the first information or the second information;

27   code for communicating at least a portion of the presentation representation from

28   the adapter to one or more devices, the communicated portion of the presentation representation

29   including one or more keyframes from the set of keyframes and a portion of the textual

30   information.

1   15.   (Currently amended): The computer program product of claim 14[[:]]

2   further comprising:

3   code for synchronizing [[the]] audio information at the adapter received from the

4   first system or from the capture device at the adapter with the selected set of keyframes.

1   16.   (Previously presented): The computer program product of claim 14

2   further comprising:

3   code for storing the set of keyframes in a memory coupled to the adapter.

1   17.   (Currently amended): The computer program product of claim 16 further

2   comprising:

3   code for receiving at the adapter a request from a device requesting transmission

4   of a first portion of the one or more keyframes in the set of keyframes;

5   in response to the request, code for determining at the adapter the first portion of

6   one or more keyframes in the set of keyframes requested by the device and corresponding audio

7   information; and

8   wherein the code for communicating at least a portion of the presentation

9   representation further comprises code for transmitting the first portion of the set of keyframes

10   and corresponding audio information from the adapter to the device.

1   18.   (Currently amended): The computer program product of claim 17 wherein

2   the request received from the device requests transmission of a portion of the first information

3   received by the adapter from the first system.

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

1   19.   (Currently amended): The computer program product of claim 17 wherein

2 the request received from the device requests transmission of <u>a portion of the second</u> information

3 received <u>by the adapter</u> from the capture device.

1   20.   (Previously presented): The computer program product of claim 17

2 wherein the request received from the device requests transmission of audio information <u>from</u>

3 <u>the first information or the second information</u> received <u>by the adapter</u> from the first system and

4 the capture device.

1   21.   (Currently amended): The computer program product of claim 17 wherein

2 the request received from the device requests transmission of video information <u>from the first</u>

3 <u>information or the second information</u> received <u>by the adapter</u> from the first system and the

4 capture device.

1   22.   (Currently amended): The computer program product of claim 17 wherein

2 the request received from the device requests transmission of audio or video information

3 received <u>by the adapter</u> from the first system and the capture device between a start time and an

4 end time.

1   23.   (Currently amended): The computer program product of claim 14 further

2 comprising<u>:</u>

3 ~~code for processing the information received from the first system and the~~

4 ~~information received from the capture device to generate a first representation;~~

5 ~~wherein the code for communicating further comprises code for transmitting at~~

6 ~~least a portion of the first representation;~~

7 ~~wherein the code for processing the information received from the first system~~

8 ~~and the information received from the capture device to generate the first representation~~

9 ~~comprises:~~

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

10   code for selecting a ~~plurality of video~~ the one or more keyframes at the adapter

11   from video information in the first information or the second information received from the first

12   system and from the capture device;

13   code for synchronizing the ~~plurality of video~~ one or more keyframes at the

14   adapter with audio information received from the first system and with audio information

15   received from the capture device; and

16   code for storing third information ~~related to~~ associating the ~~plurality of video~~ one

17   or more keyframes with the audio information received from the first system, the audio

18   information received from the capture device, and the portion of textual information.

1   24.   (Currently amended): The computer program product of claim 23 ~~wherein~~

2   ~~the code for processing the information received from the first system and the information~~

3   ~~received from the capture device to generate the first representation~~ further ~~comprises~~

4   comprising:

5   code for generating a web page for each ~~video~~ keyframe in the ~~plurality of video~~

6   one or more keyframes, each web page including a video frame;

7   code for assigning a uniform resource locator (URL) to each web page; and

8   wherein the code for ~~transmitting~~ communicating at least a portion of the ~~first~~

9   presentation representation comprises code for transmitting at least one URL assigned to a web

10   page.

1   25.   (Currently amended): The computer program product of claim 24 ~~wherein~~

2   ~~the code for transmitting at least a portion of the first representation comprises~~ further

3   comprising:

4   code for receiving a request at the adapter from a device identifying a first URL;

5   in response to the request, code for determining at the adapter a first web page

6   corresponding to the first URL; and

7   wherein the code for communicating at least a portion of the presentation

8   representation comprises code for transmitting the first web page from the adapter to the device.

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

1   26.   (Currently amended): The computer program product of claim 23 wherein

2 the code for ~~transmitting at least a portion of the first representation~~ analyzing the first

3 information and the second information at the adapter to extract textual information from the first

4 information or the second information using one or more recognition techniques comprises:

5   ~~code for receiving a request from a device requesting transmission of a set of~~

6 ~~video frames from the plurality of video frames; and~~

7   ~~in response to the request, code for transmitting the set of video frames to the~~

8 ~~device~~

9   code for generating the portion of the textual information at the adapter from the

10 audio information received from the capture device in response to a speech recognition

11 technique;

12   code for identifying a speaker associated with the audio information received

13 from the capture device at the adapter based on a voice recognition technique; and

14   wherein storing the third information comprises annotating the textual

15 information in the presentation representation at the adapter with information associated with the

16 identified speaker.

1   27.   (Currently amended): A system for communicating information received

2 during a multimedia presentation, the system comprising:

3   a processor; and

4   a memory coupled to the processor and configured to store a set of program

5 modules executable by the processr, the program modules comprising:

6   an input module configured to: ~~; and~~

7   receive first information from a first system, the first information

8 including at least one of video information or audio information generated from a presentation

9 file,

10   receive second information from a capture device, the secnd

11 information including at least one of video information or audio information captured by the

12 capture device during the multimedia presentation;

13   a processing module configured to:

14   analyzing video information received from the first system or

15   video information received from the capture device to determine a difference between a first

16   video frame and a second video frame,

17   select a set of one or more keyframes from the analyzed video

18   information received from the first system or the analyzed video information received from the

19   capture device based on the difference between a first video frame and a second video frame in

20   response to a user-configurable threshold,

21   analyze the first information and the second information to extract

22   textual information from the first information or the second information using one or more

23   recognition techniques, and

24   generate a presentation representation of the first information and

25   the second information, the presentation representation including a representation of each

26   keyframe in the set of keyframes and the textual information extracted by the presentation

27   recorder device from the first information or the second information; and

28   a communication module configured to communicate at least a portion of

29   the presentation representation to one or more devices, the communicated portion of the

30   presentation representation including one or more keyframes from the set of keyframes and a

31   portion of the textural information [[;]]

32   ~~wherein the input module is configured to:~~

33   ~~receive at least one of audio or video information from a first system, the~~

34   ~~at least one of video information or audio information generated from a presentation file;~~

35   ~~receive information from a capture device, the information received from~~

36   ~~the capture device comprising at least one of audio or video information captured by the~~

37   ~~capture device during the multimedia presentation;~~

38   ~~perform differencing between a first video frame from a second video~~

39   ~~frame of the video information received from the first system or the capture device;~~

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

40   ~~select based on the differencing, a set of one or more keyframes from the~~

41   ~~video information received from the first system or the capture device in response to a~~

42   ~~user-configurable threshold; and~~

43   ~~wherein the communication module is configured to communicate one or more~~

44 ~~keyframes of the set of keyframes~~.

1   28.   (Currently amended): The system of claim 27 wherein[[:]] the ~~input~~

2 <u>processing</u> module is further configured to synchronize [[the]] audio information received <u>from</u>

3 <u>the first system or the capture device</u> ~~at the adapter~~ with the selected set of keyframes.

1   29.   (Currently amended): The system of claim 27 wherein the ~~input~~

2 <u>processing</u> module <u>is further</u> ~~includes a processor~~ configured to store the <u>selected</u> set of

3 keyframes in a ~~memory~~ <u>storage device</u> ~~coupled to the input module~~.

1   30.   (Currently amended): The system of claim 29 <u>wherein the processing</u>

2 <u>module is</u> further configured to<u>:</u>

3   receive a request from a device requesting transmission of ~~a first portion of~~ <u>the</u>

4 <u>one or more keyframes in</u> the set of keyframes<u>;</u>[[,]] ~~and wherein:~~

5   ~~the processor is configured to~~ determine<u>, in response to the request,</u> the ~~first~~

6 ~~portion of~~ <u>one or more keyframes in</u> the set of keyframes requested by the device and

7 corresponding audio information; and

8   <u>wherein</u> the communication module is <u>further</u> configured to communicate <u>at least</u>

9 <u>a portion of the presentation representation by transmitting</u> the ~~first portion of the set of~~

10 ~~keyframes and~~ corresponding audio information to the device.

1   31.   (Currently amended): The system of claim 30 wherein the request

2 received from the device requests transmission of <u>a portion of the first</u> information received from

3 the first system.

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

1   32.   (Currently amended): The system of claim 30 wherein the request
2 received from the device requests transmission of <u>a portion of the second</u> information received
3 from the capture device.

1   33.   (Currently amended): The system of claim 30 wherein the request
2 received from the device requests transmission of audio information <u>from the first information or</u>
3 <u>the second information</u> received from the first system and the capture device.

1   34.   (Currently amended): The system of claim 30 wherein the request
2 received from the device requests transmission of video information <u>from the first information or</u>
3 <u>the second information</u> received from the first system and the capture device.

1   35.   (Previously presented): The system of claim 30 wherein the request
2 received from the device requests transmission of audio or video information received from the
3 first system and the capture device between a start time and an end time.

1   36.   (Currently amended): The system of claim 29 wherein the ~~processor~~
2 <u>processing module</u> is further configured to<u>:</u>
3   select the <u>one or more keyframes in the</u> set of keyframes as a plurality of video
4 frames from video information received by the input module<u>;</u>[[,]]
5   ~~to~~ synchronize the plurality of video frames with audio information received <u>from</u>
6 <u>the first system and with audio information received from the capture device</u> by the input
7 module<u>;</u>[[,]] and
8   ~~to~~ store <u>third</u> information ~~related to~~ <u>associating</u> the plurality of video frames <u>with</u>
9 <u>the audio information received from the first device, the audio information received from the</u>
10 <u>second device, and the portion of the textual information</u>.

1   37.   (Currently amended): The system of claim 36 wherein[[:]] the ~~processor~~
2 <u>processing module</u> is <u>further</u> configured to:

3   generate a web page for each video frame in the plurality of video frames,

4 each web page including a video frame.[[;]] and

5   assign a uniform resource locator (URL) to each web page; and

6   <u>wherein</u> the communication module is <u>further</u> configured to communicate at least

7 <u>a portion of the presentation representation by transmitting at least</u> one URL assigned to a web

8 page.

1   38.   (Currently amended): The system of claim 37 <u>wherein the processing</u>

2 <u>module is</u> further configured to<u>:</u>

3   receive a request from a device identifying a first URL, <u>and</u>[[,]] ~~and wherein:~~

4   ~~the processor is configured to~~ determine<u>, in response to the request,</u> a first web

5 page corresponding to the first URL; and

6   <u>wherein</u> the communication module is <u>further</u> configured to communicate <u>at least</u>

7 <u>a portion of the presentation representation by transmitting</u> the first web page to the device.

1   39.   (Currently amended): The system of claim 36 <u>wherein the processing</u>

2 <u>module is</u> further configured to<u>:</u>

3   receive a request from a device requesting transmission of a set of video frames

4 from the plurality of video frames<u>;</u>[[,]] and

5   wherein, in response to the request, the communication module is <u>further</u>

6 configured to <u>communicate at least a portion of the presentation representation by</u> transmit<u>ting</u>

7 the set of video frames to the device.

1   40.   (Currently amended): A method of communicating information received

2 during presentation of information from a presentation file, <u>the method</u> comprising:

3   ~~providing a physical adapter;~~

4   receiving, at ~~the physical~~ <u>a presentation</u> adapter, at least one of video information

5 or audio information from a first data processing system communicably coupled to the ~~physical~~

6 <u>presentation</u> adapter, the at least one of video information or audio information received during

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

7 presentation of the information from the presentation file and generated as a result of outputting

8 contents of the presentation file;

9 ~~differencing between a first video frame and a second video frame, at the physical~~

10 ~~adapter, of the video information received from the first data processing system~~ analyzing, at the

11 presentation adapter, video information received from the first data processing system to

12 determine a difference between a first video frame and a second video frame;

13 selecting, at the presentation adapter, ~~based on the differencing, at the physical~~

14 ~~adapter,~~ a set of one or more keyframes ~~based at least upon~~ from the analyzed video information

15 received from the first data processing system based on the difference between a first video

16 frame and second video frame in response to a user-configurable threshold; ~~and~~

17 analyzing, at the presentation adapter, audio information received from the first

18 data processing system to extract textual information using one or more recognition techniques;

19 generating, at the presentation adapter, a representation of the presentation file

20 including a representation of each keyframe in the set of keyframes and the textual information

21 extracted from the audio information;

22 transmitting the representation of the presentation file from the presentation

23 adapter including one or more keyframes of the set of keyframes and a portion of the textual

24 information to a second data processing system, wherein the second data processing system is

25 enabled to output the ~~information~~ at least a portion of the representation of the presentation file

26 received from the presentation adapter.

1 41. (Currently amended): The method of claim [[1]] 40 wherein ~~differencing~~

2 ~~between a first video frame and a second video frame~~ analyzing the video information received

3 from the first data processing system comprises:

4 comparing a first frame of video to a subsequent second frame of video; ~~and~~

5 identifying the second frame as different from the first frame; and ~~further~~

6 ~~comprising~~

7 storing both the first frame of video and the second frame of video.

Appl. No. 09/728,453
Amdt. dated October 15, 2008
Reply to Office Action of April 15, 2008

PATENT

1   42.   (Currently amended): The method of claim 41 wherein <u>comparing a first</u>
2 <u>frame of video to a subsequent second frame of video</u> ~~identifying the second frame of video as~~
3 ~~different from the first frame of video comprises~~:
4   <u>comparing image pixels of the first frame of video and the second frame of video</u>
5 <u>or comparing results of optical character recognition (OCR) with the first frame and results of</u>
6 <u>OCR with the second frame.</u>
7   ~~comparing the difference between the second frame of video and the first frame of~~
8 ~~video a predetermined threshold.~~

1   43.   (Currently amended): The method of claim [[41]] <u>40</u> wherein <u>analyzing</u>
2 <u>audio information received from the first data processing system comprises</u>:
3   <u>determining a portion of the textual information in response to applying speech</u>
4 <u>recognition at the presentation adapter to the audio information.</u>
5   ~~wherein identifying the second frame of video as different from the first frame of~~
6 ~~video comprises comparing image pixels of the first frame of video and the second frame of~~
7 ~~video.~~

1   44.   (Currently amended): The computer program product of claim 14 wherein
2 the code for <u>analyzing the video information received from the first system or video information</u>
3 <u>received from the capture device</u> ~~differencing between a first video frame and a second video~~
4 ~~frame~~ comprises<u>:</u>
5   code for comparing a first frame of video to a subsequent second frame of video<u>;</u>
6 ~~and~~
7   <u>code for</u> identifying the second frame as different from the first frame; <u>and</u>
8   ~~further comprising~~ code for storing both the first frame of video and the second
9 frame of video.

1   45.   (Currently amended): The computer program product of claim 44 wherein

2 the code for comparing a first frame of video to a subsequent second frame of video identifying

3 the second frame of video as different from the first frame of video comprises:

4   code for comparing image pixels of the first frame of video and the second frame

5 of video or comparing results of optical character recognition (OCR) with the first frame and

6 results of OCR with the second frame.

7   code for comparing the difference between the second frame of video and the first

8 frame of video to a predetermined threshold.

1   46.   (Currently amended): The computer program product of claim [[45]] 14

2 wherein the code for analyzing audio information received from the first data processing system

3 comprises:

4   code for determining a portion of the textual information in response to applying

5 speech recognition at the presentation adapter to the audio information.

6   identifying the second frame of video as different from the first frame of video

7 comprises code for comparing image pixels of the first frame of video and the second frame of

8 video.

1   47.   (Previously presented): The computer program product of claim 14

2 wherein the code for selecting the set of keyframes in response to the user-configurable threshold

3 comprises code for selecting frames of video at a predetermined sampling interval.